SWITCHING POWER ADAPTER FOR LEDs



CE

Туре:	SWITCHING POWER ADAPTER for LEDs 36W 24V
Input voltage :	90÷264 V AC (50-60Hz)
Output voltage:	24 V DC
Maximum output current:	1,5 A
Maximum power:	36 W
Standby power:	Max 0,5 W
Power efficiency:	Level IV
Type of power plug:	Interchangeable plugs for Euro and USA
Type of output connection:	Female socket foreseen for connectors M79- or M79C-
In conformity to the standards:	EN61347-1 - EN61347-2-13 EN61000-3-2 - EN61000-4-2

LEDs 36W 24V 0÷264 V AC (50-60Hz) 4 V DC 5 A w ax 0,5 W vel IV terchangeable plugs for Europe, d USA male socket foreseen for nnectors M79- or M79C-I61347-1 - EN61347-2-13 - EN55015 - EN61547 -EN61000-3-2 - EN61000-4-2 / UL8750 / GB19510 -

In conformity to the requirements of the directives and regulations:

Approval marks:

2009/125/EC cULus CCC

2014/35/EU - 2014/30/EU -



Europe plug

USA plug

GB17743





· Interchangeable plugs supplied as accessories:

United Kingdom plug







- · Outgoing connection foreseen with female socket for connector M79 (ref. page 805) or M79C (ref. page 805.1)
- Table of the available colours:
- N = black

















Interchangeable plug



M79



H





102.0

36,0 ±1



Е