

# MULTI-CONDUCTOR CABLES INSULATED IN FEP + FEP T200°C cURus + ROUND SHEATH IN PVC

**XB---**

2008



Type of insulation:

**FEP + FEP UR STYLE 21167  
+ external sheath in round PVC**

Working temperature:

**T 200°C  
T 60°C for the PVC**

Type of conductor:

**NICKEL-PLATED COPPER  
600 V**

Working voltage:

Inner cable in conformity to the standard:

**UL 758 AWM STYLE 21167**

Approval marks:

**cURus**(for the inner cable in FEP+FEP)



**PROCESSED WIRE** **FILE E221012**

**RESPOOLED WIRE** **FILE E221012**

• AWG table of the cores:

Code	AWG	Conductor strand	Cores colours*	Cores position	Shape	Dimension ±0,2 mm
<b>XB28-</b>	2 x 18	48 x 0,161	tn tb	P	round	ø 6,0
<b>XB38-</b>	3 x 18	48 x 0,161	tn tb + ground	P	round	ø 6,0

• Other AWG on request.

\* Table of the lines colours to identify the cores:

tn = black                      tb = white

\* Cores position table:





P = parallel

**XC--T:** version with insulated 24 AWG steel self-supporting wire rope, with 35 kg breaking load.

• AWG and multiple table of the cores for the version with steel wire rope:

Code	AWG	Conductor strand	Cores colours*	Cores position	Shape	Dimension ±0,2 mm
<b>XC28-</b>	2 x 18	48 x 0,161	tn tb	P	round	ø 6,1
<b>XC38-</b>	3 x 18	48 x 0,161	tn tb + ground	P	round	ø 6,4

• UR approval printing of the inner cable, on the sheath, with white ink.



• Table of available colours:

**T** = transparent (sheath and cores)

**N** = black

**B** = white

- Other colours on request.

